

Thermal Printer

TP-260

- High-Speed Printing!
- Print receipts easily with this Poslab TP-260 Thermal Receipt Printer!
- It features a line thermal print method with up to 260 mm per second print speed and a 203 dpi (8 dots/mm) resolution.
- SeiKo SII Pring Mechanism.



Specification	
Printing	Method Direct Thermal
Print width	76mm
Print speed	260mm/s
Interface	RS-232C/Parallel/USB/LAN
Paper width	79.5±0.5mm(W)*83mm(Diameter)
Line spacing	3.75mm (adjustable b\ command)
Columns	80mm paper Font A: 12 x 24, Font B: 9 x 17, Simplified & Traditional Chinese/Japanese/Korea: 24 x 24
Flash	256K bytes
Life	Reliability100km
Cash Drawer	DC 24V / 1A
Weight	1.7KG
Dimension	190 x 145 x 150 mm (WxHxD)
Barcode	
Extension character table	PC347 (Standrd Europe),Katakana,PC850(Multilingual) PC860(Portuguese),PC863(Canadian-French), PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252, PC866(Cyrillic2), PC 852(Latin2),PC858,Latvian,Arabic,PT151(1251)
Barcode type	UPC-A / UPCE / JAN13(EAN13) / JAN8(EAN8) / CODE39/ITF / ODABAR / CODE93 / CODE128
Buffer	Input buffer 128k bytes
Power	
Input buffer Input	AC 110V/220V, 50-60Hz
Power adapter Output	DC 24V / 2.5A
Environment	
Working temperature	0~45°C,humidity : 10~80%
Store temperature	0~60°C,humidity : 10~90%
Regulatory	
EMC & Safety	CE, FCC

