

# UltraCard™ Non-Technology Cards

## High-Quality, Non-Technology Cards for a Variety of Applications

Graphics-quality UltraCard non-technology cards feature polished, scratch- and debris-reduced surfaces to optimize the quality of printed images and text on your finished credentials.

Available in a variety of sizes and compositions — and compatible with HID inkjet printers or any brand of direct-to-card (DTC™) or retransfer printers — UltraCard products are great for full-color photo ID, gift and loyalty cards and come in a breadth of options to meet virtually any non-technology card printing need.

### ULTRACARD

Compatible with HID inkjet or any DTC printer, standard UltraCard 30 mil PVC cards are manufactured not only to ensure clean, scratch-free, high-quality prints but also to extend DTC printhead life. 30 mil PVC cards are available in standard, high- and low-coercivity magnetic stripe varieties.

The UltraCard line also offers versatile, low-cost, 10 mil PVC options that include both standard and adhesive-backed cards. Standard 10 mil cards are ideal for use as business cards where adhesive Mylar®- and paper-backed cards allow users to print a photo ID, remove the backing and then adhere the photo ID to an existing credential such as a clamshell proximity technology card.

### ULTRACARD PREMIUM

Available as standard or with a high-coercivity magnetic stripe, UltraCard Premium is the preferred card for a variety of applications. Compatible with both DTC and retransfer card printers with or without lamination, UltraCard Premium's composite material construction provides

enhanced durability over PVC, ensuring cards stand up to the rigors of heated retransfer and lamination rollers during the card printing process. For organizations that desire highly durable, longer-lasting credentials that naturally resist warpage and cracking, UltraCard Premium is an excellent choice.

### ULTRACARD PC

Made of a 100% polycarbonate construction, UltraCard PC offers the highest level of card durability and longest card life within the UltraCard family of cards. Highly resilient UltraCard PC cards are ideal for retransfer printing and/or laser engraving applications. Moreover, because polycarbonate is more environmentally friendly than commonly used PVC constructions, UltraCard PC can play a pivotal role in your organization's green initiatives.

For highly durable, sharp-looking credentials, choose quality-constructed UltraCard non-technology cards.



## OPTIONS

### UltraCard

- CR-80 30 mil PVC cards with or without magstripe
- CR-79 or CR-80 10 mil PVC cards available standard or adhesive-backed

### UltraCard Premium

- CR-80 30 mil premium composite cards with or without magstripe

### UltraCard PC

- CR-80 30 mil 100% polycarbonate cards

# UltraCard Non-Technology Cards



## ULTRACARD NON-TECHNOLOGY CARDS OFFER:

- Quality
- Durability
- Versatility

Card Type	UltraCard	UltraCard Premium	UltraCard PC
<b>Card Size (Dimensions)</b>	CR-80 (3.375"L x 2.125"W / 85.6 mm L x 54 mm W) CR-79* standard or adhesive back (3.313"L x 2.063"W / 84.1 mm L x 52.4 mm W)	CR-80 (3.375"L x 2.125"W / 85.6 mm L x 54 mm W)	
<b>Card Construction</b>	100% PVC	Composite polyester construction	100% Polycarbonate
<b>Available Configurations</b>	<ul style="list-style-type: none"> <li>• CR-80 30 mil standard</li> <li>• CR-80 30 mil with low-coercivity (300 Oe) magnetic stripe</li> <li>• CR-80 30 mil with high-coercivity (2750 Oe) magnetic stripe</li> <li>• CR-80 10 mil standard</li> <li>• CR-80 10 mil adhesive Mylar-backed</li> <li>• CR-80 10 mil adhesive paper-backed</li> <li>• CR-79* 10 mil adhesive Mylar-backed</li> <li>• CR-79* 10 mil adhesive paper-backed</li> </ul>	<ul style="list-style-type: none"> <li>• CR-80 30 mil standard</li> <li>• CR-80 30 mil with high-coercivity (2750 Oe) magnetic stripe</li> </ul>	<ul style="list-style-type: none"> <li>• CR-80 30 mil</li> </ul>
<b>Printing Compatibility</b>	<ul style="list-style-type: none"> <li>• Direct-to-Card (all brands)</li> <li>• HID FARGO INK1000 solvent inkjet</li> <li>• HID ELEMENT UV-cured inkjet</li> </ul>	<ul style="list-style-type: none"> <li>• Direct-to-Card (all brands)</li> <li>• Retransfer (all brands)</li> <li>• HID ELEMENT UV-cured inkjet</li> </ul>	<ul style="list-style-type: none"> <li>• Retransfer (all brands)</li> <li>• HID ELEMENT UV-cured inkjet</li> </ul>
<b>Laser Engraving Compatibility</b>	Not compatible		Compatible
<b>Recommended Storage Conditions</b>	Humidity: 40 - 70% relative humidity Temperature: 60° - 85° F (15° - 30° C)		

\* CR-79 cards are slightly smaller than CR-80 cards; designed for adhesion to the inside edge of standard CR-80 proximity cards



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 | Latin America: +52 (55) 9171-1108

**For more global phone numbers click here**

© 2022 HID Global Corporation/ASSA ABLLOY AB. All rights reserved.

2015-09-13-si-fargo-ultracard-nontechnology-ds-en PLT-00078

Part of ASSA ABLLOY