



The digital compact camera
for tough applications:
Under water, at work, in
sports or in leisure time

	ART. CODE	EAN
RICOH WG-80 BLACK	03122	0027075304383
RICOH WG-80, ORANGE	03127	0027075304420

This standard-class waterproof digital compact camera is designed so that anyone can capture the fun and excitement of various outdoor activities more casually and effortlessly, and without worries.

Despite its compact, lightweight body, the WG-80 offers outstanding basic specifications that outperform ordinary digital cameras and smartphones under demanding outdoor conditions. It is waterproof to a depth of 14 meters; shockproof against a fall from a height of 1.6 meters; and freeze-proof against temperatures as low as -10°C.

It also features a six-LED Macro Lights unit whose maximum illumination intensity has been upgraded to almost twice that of its predecessor. This unit even allows the photographer to adjust the illumination level for improved operability in close-range photography.

- 16 Megapixel Backside Illuminated 1/2.3" CMOS sensor
- 28-140mm zoom lens (equivalent in 35mm format)
- Sturdy and robust body construction (waterproof up to 14 meters, for up to two hours, old-resistant to -10°C, shockproof to 1.6 m and breakproof to 100 kg)
- Macro function with digital microscope function from 1 cm shooting distance
- Six LED lights for macro shooting and selfie mode, with variable light intensity
- Digital zoom and Intelligent Zoom function up to a total focal length of 1,008 mm (equivalent in 35mm format)
- Multiple electronic "Shake Reduction" to prevent blurred shots 25 scene modes for a wide range of shooting situations
- Underwater shooting mode, specifically designed for underwater photography
- Full HD video with 30 frames/second in H.264 format
- Face detection for up to 32 faces, with automatic shutter release when a smile is detected, and closed-eye warning
- Macro stand (included) to maintain a minimum focusing distance of one centimeter
- Receiver for the optional IR remote control on the front and back of the camera
- Outdoor-friendly Style Watch function to display the time on the LCD monitor, using an extended push of the OK button when the camera's power is turned off

Kit Accessories

RECHARGEABLE LI-ION BATTERY D-LI92	39800	0027075049116
POWER ADAPTER		
POWER PLUG		
USB CABLE-USB157	37019	0027075288515
CARABINER STRAP O-ST104	39857	0027075183285
MACRO STAND O-MS1	39004	0027075188860

Optional Accessories

BATTERY CHARGER KIT K-BC183E	30289	0027075303386
CAMERA CASE O-CC135	38859	0027075225848
CAMERA CASE O-CC118	39945	0027075207714
PROTECTOR JACKET O-CC1252	39986	0027075216303
REMOTE CONTROL E	37376	0027075049024
REMOTE CONTROL F	37377	0027075049031
REMOTE CONTROL O-RC1	39892	0027075183513
SPORT STRAP O-ST81	39457	0027075118324
WG FLAT ADHESIVE MOUNT O-CM1471	37030	0027075276017
WG HANDLE BAR MOUNT O-CM1472	37031	0027075276024
WG SUCTION CUP MOUNT O-CM1473	37032	0027075276031
WG HOLDER O-CH1470	37033	0027075276048
LARGE ADHESIVE MOUNT O-CM1532	37041	0027075287778
WRIST STRAP MOUNT O-CM1533	37042	0027075287785
PEG MOUNT O-CM1534	37043	0027075287792
MAGNET MOUNT O-CM1535	37044	0027075287808
HELMET STRAP MOUNT O-CM1536	37045	0027075287815
ANGLE ADAPTER O-MA1532	37047	0027075287839

Packaging

SIZE	175 (B) x (H) 138 x (L) 83 mm
WEIGHT	493,1 gr



ADHESIVE MOUNT O-CM1532



WG HANDLE BAR MOUNT
O-CM1472



HELMET STRAP MOUNT O-CM1536

RICOH WG-80

CAMERA TYPE

TYPE Water protected Digital compact camera for movie and photo

SENSOR

TYPE 1/2.3" CMOS
 EFFECTIVE: approx. 16 megapixels
 PIXELS STANDARD OUTPUT: AUTO, Manual (ISO 125 - 6400)
 SENSITIVITY Still: Pixel Track SR, Digital SR, mode by automatically increasing sensitivity up to ISO 6400
 MOTION BLUR REDUCTION Video: Movie shake reduction mode (Movie SR)
 WHITE BALANCE Auto, Daylight, Shade, Cloudy, Tungsten light, Fluorescent light(D:Daylight Color, N:Daylight White, W:White Light), Ring light, Manual
 DYNAMIC RANGE Shadow/Highlight adjustment
 NOISE REDUCTION Automatically applied when the shutter speed is slower than 0.25 s

FILE FORMATS

STILL JPEG (conforms to Exif 2.3), conforms to DCF2.0, PRINT Image Matching III
 RECORDED PIXELS STILL: Size: 16MP, 12MP (1:1), 12MP(16:9), 7MP, 5MP(16:9), 5MP, 4MP(16:9), 3MP, 2MP(16:9), 1024, 640
 Selection limited by mode
 STILL: ★★★, ★★, ★, SD/SDHC/SDXC Memory Card
 BUILT-IN MEMORY Approx. 68MB,

LENS

LENS DESIGN RICOH lens 11 elements in 9 groups (5 aspherical elements)
 FOCAL LENGTH 5 - 25mm
 35MM FORMAT EQUIVALENT Approx. 28 - 140mm
 MAXIMUM APERTURE F3.5(W) – F5.5(T)
 CONSTRUCTION RICOH lens, 11 elements in 9 groups (5 aspherical elements)
 OPTICAL ZOOM 5x
 DIGITAL ZOOM Approx. 7.2x
 INTELLIGENT ZOOM Approx. 7.5X at 7M, approx. 36X at 640 (including optical zoom)
 MAXIMUM MAGNIFICATION Approx. 0.4x (1cm Macro)

AUTO FOCUS SYSTEM

TYPE 9-point AF, Spot AF, Auto tracking AF,
 FOCUS RANGE Standard: 0.5m - infinity / 1.64ft. - infinity (entire zoom range)
 Macro:0.1 - 0.6m / 0.33 - 1.97ft. (entire zoom range)
 1cm Macro:0.01 - 0.3m / 0.03 - 0.98ft. (middle zoom position)
 Infinity-landscape, Pan Focus, Manual Focus: available
 0.01m - infinity (Depends on the zooming steps. 0.01m is only available in 2 - 4 zoom step.)
 MANUAL FOCUS RANGE Face Detection AF&AE is available for all modes up to 30 faces. Smile Capture, Self-portrait Assist, Self-portrait Assist + Smile Capture, Blink Detection
 FACE DETECTION Detect up to 1 pet's face(auto)
 PET DETECTION available
 AF ASSIST LAMP available

EXPOSURE CONTROL

METERING SYSTEM Multi-segment metering, Center-weighted metering, Spot metering
 SHUTTER SPEED 1/4000 - 1/4sec (Mechanical and electronic shutter),
 4sec at most. (Night Scene mode setting)
 EV COMPENSATION ± 2EV (1/3EV steps)
 SCENE MODE Auto Picture, Program, HDR, Handheld Night Snap, Movie, High Speed Movie, Digital Microscope, Landscape, Flower, Portrait, Underwater, Underwater Movie, Interval Shot, Interval Movie, Surf & Snow, Kids, Pet, Sport, Night Scene, Night Scene Portrait, Fireworks, Food, Digital SR, Report, Green
 SELF TIMER 10 sec., 2 sec., OFF

CAPTURE SETTING

IMAGE TONE Bright, Natural, Vibrant, Slide Film, Monochrome, Cross Processing

DISPLAY

TYPE 2.7" Wide LCD, approx. 230K dots, AR Coating(Cover only),
 With outdoor mode to adjust the brightness of the monitor for the respective lighting conditions

SHOOTING FEATURES

DRIVE MODES One shot, Self-timer, Continuous Shooting, Burst Shooting, M Continuous, S Continuous, Remote Control, Auto Bracketing
 CONTINUOUS SHOOTING Approx. 1.08 frame/sec., max 69 # of frames

BUILT-IN FLASH

MODES Flash-on and Flash-off modes.
 "Red-eye" compensation function employs a pre-discharge.
 FLASH RANGE Wide:approx. 0.2 - 5.5m / 0.66 - 18 ft. (ISO Auto)
 Tele:approx. 0.2 - 3.5m / 0.66 - 11 ft. (ISO Auto)
 6 LED RING LIGHTS Single touch Ring light mode, Bright Illumination
 Able to adjust amount of light by 10 steps
 Able to select which LED should be lighted by 5 patterns
 Macro shooting from 1cm

MOVIE

FILE FORMAT MPEG-4 AVC/H.264
 NUMBER OF RECORDED PIXELS 1920 (1920 x 1080) : approx. 30fps,
 1280 (1280 x 720) : approx. 60/30fps
 AUDIO [Movie/Underwater Movie] 32KHz, 16bit, monoaural
 [High Speed Movie] 8KHz, 16bit, monoaural
 SHAKE REDUCTION Movie shake reduction mode (Movie SR)
 MOVIE EDIT FUNCTIONS Save as still image, Divide Movies, Adding title picture

PLAYBACK

PLAYBACK FUNCTIONS One Shot, Index (6 thumb nails, 12 thumb nails), Enlargement (up to 10X, scroll available), Movie Playback, Histogram, Folder display, Select&Delete, Calendar

PLAYBACK MODES

Slideshow, Image Rotation, Small Face Filter, Ink Rubbing Filter, Collage, Digital Filter(B&W / Sepia, Toy Camera, Retro, Color, Extract Color, Color Emphasis, High Contrast, Starburst, Soft, Fish-eye, Brightness, Miniature), HDR Filter, Original Frame, Movie Edit, Red-eye Edit, Resize, Cropping, Image Copy, Protect, Start-up Screen

DIGITAL FILTER

B&W / Sepia, Toy Camera, Retro, Color, Extract Color, Color Emphasis, High Contrast, Starburst, Soft, Fish-eye, Brightness, Miniature Filter

CUSTOMIZATION

LANGUAGES English, French, Germany, Spanish, Portuguese, Italy, Dutch, Japanese, Danish, Swedish, Finnish, Polish, Czech, Hungarian, Turkey, Greek, Russian, Thai, Korean, Simplified Chinese, Traditional Chinese

SPECIAL

WORLD TIME Supported
 DATE IMPRINT Date Imprint Available (Date, Time, Date & time) (except Green)
 START-UP TIME Approx. 1.5 sec (TBD)
 RELEASE TIME LAG Approx. 0.008 sec.
 WATER PROOF Up to 14m (45ft.) for 2 hours
 Equivalent to JIS Class 8 waterproof

DUSTPROOF

SHOCK PROOF IP6X / JIS Class 6 dustproof capabilities

OPERATING TEMPERATURE

−10°(14°F) to 40°(104°F)

POWER SUPPLY

POWER SOURCE Rechargeable lithium-ion battery D-LI92
 BATTERY LIFE Still*: approx. 300 shots (Rechargeable Lithium-ion battery)
 Playback**: approx. 260 min. (Rechargeable Lithium-ion battery) (TBD)
 Movie: approx. 90 min. ** (TBD)
 * Recording capacity shows approximate number of shots recorded during CIPA-compliant testing. Actual performance may vary depending on operating conditions.
 ** According to the result of RICOH IMAGING in-house testing.

BATTERY CHARGE TIME

Approx. 120 min.

INTERFACES

USB2.0(Micro-B), HDMI output terminal(Type D)

DIMENSIONS & WEIGHT

DIMENSIONS Approx. 122.5 (W) x 61.5 (H) x 29.5mm (D) /4.8 (W) x 2.4 (H) x 1.2inches (D) (including lens depth)
 WEIGHT Approx. 193g / 6.8 oz. (loaded and ready)
 Approx. 173g / 6.1oz. (without battery and SD memory card)

SYSTEM REQUIREMENTS

PC Windows® 7, Windows® 8.1, Windows® 10
 MAC Mac OS X 10.10, 10.11, 10.12, 10.13, 10.14, 10.15

